

Helos™20

ARCH. SERIES

IN-CEILING STEREO/HOME THEATER FRONT/CENTER/SURROUND

## HIGH-PERFORMANCE STEREO SOUND FROM A SINGLE IN-CEILING SPEAKER

Helos 20 delivers stereo sound from a single speaker, ideal for use in small rooms such as bathrooms, offices, and kitchens. Helos 20 also bridges to deliver wide dispersion mono sound reproduction. Featuring dual 0.75-inch neodymium soft dome tweeters, a high-rigidity aluminum cone woofer, and proprietary Vojtko crossover topology, Helos 20 effortlessly provides solid imaging with extreme sonic accuracy.

Frequency Response  $47-20,000 \text{ Hz} \pm 3\text{dB}$ 

Aiming Pivoting Tweeter Stem
Sensitivity 89 dB/2.83 volts/meter

Impedance Mono: 4 Ohms. Stereo: 8 Ohms x 8 Ohms. Compatible with 4, 6, or 8 Ohm rated amps.

Crossover Frequency 2600 Hz

High Frequency Drivers Two 0.75" (1.9 cm) neodymium soft dome

Mid/Low Frequency Driver 6.5" (16.5 cm) aluminum cone

Recommended Amplifier Power Mono: 20–200 watts

Stereo: 20 x 20 - 100 x 100 watts

Weight 4.5 lbs. (2 kg)

Diameter 9.5" (24.2 cm)
Projection From Ceiling Surface 0.4" (1 cm)
Required Ceiling Opening 8.35" (21.2 cm)



The Great American Speaker Company www.martinlogan.com

## Application:

Single stereo speaker or mono wide dispersion speaker for home theater surround or distributed audio in small rooms such as kitchens & bathrooms.

Helos 20 in-ceiling speakers deliver legendary MartinLogan quality and performance in a compact, highresolution in-ceiling loudspeaker.

## **Key Features:**

- Stereo sound from one speaker
- Tweeters aim at listening position
- High-resolution tweeter
- Low-distortion 6.5-inch aluminum cone woofer
- Precision Vojtko<sup>TM</sup> crossover
- Quick, no-hassle installation
- Paintable frame and grill cover

## **FINISH OPTIONS**





